(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication: \$1.07.1996 Bulletin 1996/31

(51) Int. Cl.6: G02F 1/136

(11)


(3)

- (21) Application number: 95100908.1
- (22) Date of filing: 23.01.1996
- (84) Designated Contracting States: CH DE FR GB LINL
- (30) Priority: 30.01.1995 JP 12298/95
- (71) Applicant: HITACHI, LTD. Chityoda-ku, Tokyo 101 (JP)
- (72) inventors:
 - Wakagi, Masatoshi
 Hitachi-shi, Ibaraki 319-12 (JP)
 - Onisawa, Kenichi Hitachinaka-shi, Ibaraki 312 (JP)

- Ando, Masahiko
 Hitachl-shi, Ibaraki 316 (JP)
- Kaneko, Toshiki
 Chiba-shi, Chiba 267 (JP)
- Minemura, Tetsuroh
 Hitachiohta-shl, Ibaraid 313 (JP)
- Okada, Tomohiro
 Hitachi-shi, Ibaraki 316 (JP)
- (74) Representative: Beetz & Partner Patentanwäite Stainsdorfstrasse 10 80538 München (DE)

(54) Liquid crystal display device and method of fabricating the same

An object of the present invention is to provide a liquid crystal display device which can be tabricated through simplified processes, provides high product yield, and is excellent in picture displaying characteristic. The liquid crystal display device of the present invention comprises a substrate (1) having thereon a plurality of drain wirings (2), a plurality of gate wirings (8) crossing the plurality of drain wirings (2) in a matrix array, a plurality of thin film transistors disposed in the vicinity of these crossings, and a plurality of pixel electrades (4) connected to the thin film transistors, respectively, a substrate disposed in opposing relation to the substrate (1), and a liquid crystal layer sandwiched between these substrates. Each terminal portion (5; 9) of the plurality of drain wirings (2) and plurality of gate wirings (8) is constructed with a metallic film covered with a transparent conductive film.



EP 0 724 183 A2